

PRODUCT DATA SHEET



MOTOROL CHASSIS GREASE

Introduction:

MOTOROL Chassis Grease - Calcium Based Grease is specially made as water resistant grease of high mechanical and thermal stability and anti rust & lubricity properties.

Applications:

- Chassis lubrication operating in moist conditions and at moderate temperatures.
- Suspension system
- Steering system
- Semi-enclosed and open gears.
- General lubrication of chains.
- Lubrication of small farm equipments

Advantages:

- Reduced friction.
- Extend bearing life.
- Increase lubrication intervals.

e

- Extreme pressure properties.
- Water resistant.
- Prevent seizure.

Performance Standard:

Meets NLGI – Grade 2, IS 507 : 1993 [Reaffirmed 2001]

Typical Specifications:

Sr. No.	Characteristics	Test Method	Specified Value
1	Appearance	VISUAL	Brown
2	NLGI consistency (Penetration) at 25°C	ASTM D 217-97	2 (265-295)
3	Drop Point °C ,Min	ASRM D 566-97	90



Environment, Health & Safety:

Every care has been taken to ensure the accuracy of the information in this PDS. This however may be affected by subsequent improvement in product (R&D). MSDS is available for all MOTOROL products on request.

MOTOROL products are unlikely to present any health and safety hazard with proper use for the correct application and maintain proper personal hygiene. Do not Spill oils on the shop floor, discharge into drains ,ground or water sources.



Plot No. 85/B-115, At-Post Karakhadi, Taluka: Padra, District: Baroda—391450, Gujarat, India Contact No: +91-2662-273373, 273727 Fax No: +91-2662-273720 Website: www.quebecoils.com Email: sales@quebecoils.com