




TRANSMATIC TYPE DXII (TRANSMISSION OIL)



Introduction:

MOTOROL TRANSMATIC DX II is a premium quality automatic transmission fluid meeting the requirement of DEXRON II and also meets Mercedes-Benz 236.1, CAT TO 2 and Allison C 4 specifications.

Applications:

- ◆ Automatic transmissions
- ◆ Power steering units
- ◆ Hydraulic systems
- ◆ Synchromesh heavy duty gear boxes
- ◆ Recommended for heavy duty trucks & off road vehicles.

Advantages:


- ◆ Excellent oxidation and thermal stability.
- ◆ Provides good dispersancy and frictional retention.
- ◆ Provides smooth and chatter free operation.
- ◆ Good EP and anti wear performance.
- ◆ Reduces maintenance cost.
- ◆ Compatible with seals.

Performance Standard:

DEXRON II, Mercedes-Benz 236.1, CAT TO 2 and Allison C 4 specifications.

Typical Specifications:

Sr. No.	Characteristics	Test Method	Typ. Value
1	Appearance	VISUAL	Bright & Clear
2	Colour	VISUAL	Red
3	Kinematic Viscosity at 100°C, cSt	ASTM D - 445	7-8
4	Viscosity Index, Min	ASTM D 2270	140
5	Flash Point, (COC), °C Min	ASTM D - 92	160
6	Pour Point, °C Max	ASTM D - 97	(-) 40



Environment, Health & Safety:

Every care has been taken to ensure the accuracy of the information in this PDS. This however may be affected by subsequent improvement in product (R&D). MSDS is available for all MOTOROL products on request.

MOTOROL products are unlikely to present any health and safety hazard with proper use for the correct application and maintain proper personal hygiene. Do not spill oils on the shop floor, discharge into drains, ground or water sources.