

PRODUCT DATA SHEET



MAGIC 4T 10W-30 (4 STROKE TWO WHELLER ENGINE OIL)

Introduction:

Motorol MAGIC 4T 10W-30 is superior quality long life high performance four stroke lubricant for new generation bikes. Formulated with high viscosity index mineral base oils and high performance additives.

Applications:

- All high performance 4 strokes two wheelers.
- Perfect choice for riders who demand top performance.
- Recommended for all modern motor cycles.

Performance Standard:

• API SJ

Advantages:

• Superior protection to engine, transmission and clutch

e

0

- Easy start and instant pick up
- Cleaner engine and batter cooling
- Provide smooth & top Performance

Typical Specifications:

Sr. No.	Characteristics	Test Method	Typ. Value
1	Appearance	VISUAL	Bright & Clear
2	Colour, Max	ASTM D 1500	3
3	Kinematic Viscosity at 100°C, cSt	ASTM D - 445	9.5-11
4	Viscosity Index, Min	ASTM D - 2270	110
5	TBN, mg KOH/g	ASTM D - 2896	4-5
6	Flash Point, (COC), °C Min	ASTM D - 92	200
	Pour Point, °C Max	ASTM D - 97	(-) 21

Environment, Health & Safety:

Every care has been taken to ensure the accuracy of the information in this PDS. This however may be affected by subsequent improvement in product (R&D). MSDS is available for all MOTOROL products on request.

MOTOROL products are unlikely to present any health and safety hazard with proper use for the correct application and maintain proper personal hygiene. Do not Spill oils on the shop floor, discharge into drains ,ground or water sources.



Plot No. 85/B-115, At-Post Karakhadi, Taluka: Padra, District: Baroda—391450, Gujarat, India Contact No: +91-2662-273373, 273727 Fax No: +91-2662-273720 Website: www.quebecoils.com Email: sales@quebecoils.com