




**AGRICULTURAL SPRAY OIL
MOTOROL SPRAY OIL**



Introduction:

MOTOROL Spray oil is manufactured with refined paraffinic low viscosity base oil.

Applications:

- ◆ Used in aerial spray in rubber plantations to control fungus
- ◆ Carrier oil for insecticide pest control
- ◆ Used for aggarbatti manufacturing
- ◆ Used in cosmetics such as hair oil, jelly etc.
- ◆ Soap cutting
- ◆ Textile lubrication & auxiliary chemicals

Advantages:

- ◆ High USR value
- ◆ Light in colour
- ◆ Low odour
- ◆ Good spreadibility
- ◆ No phytotoxicity
- ◆ Low viscosity for spray application

Performance Standard:

Proprietary grade

Typical Specifications:

Sr. No.	Characteristics	Test Methods	Typ. Value
1	Colour, Max	ASTM D 1500	0.5
2	Kinematic Viscosity at 40 °C, cSt	ASTM D 445	3.5-5.0
3	Flash Point, °C Min	ASTM D 92	110
4	Pour Point, °C Max	ASTM D 97	-9

Environment, Health & Safety:

Every care has been taken to ensure the accuracy of the information in this PDS. This however may be affected by subsequent improvement in product (R&D). MSDS is available for all MOTOROL products on request.

MOTOROL products are unlikely to present any health and safety hazard with proper use for the correct application and maintain proper personal hygiene. Do not spill oils on the shop floor, discharge into drains, ground or water sources.